

## RP971A Ratio Relay

### SPECIFICATION DATA



### FEATURES

- Adjustable pilot start point pressures
- Two pilot pressure spans available
- Four sharp barb air connections
- Molded plastic construction with neoprene diaphragms and stainless steel valve seats
- 100 mesh stainless steel screens in main and branch ports
- Designed for in-line mounting but can be wall or panel mounted

### GENERAL

The RP971A Ratio Relay is a four port nonbleed pneumatic relay which produces a modulating pressure output proportional to pilot input changes. It is used to control pneumatic valve or damper actuators in sequence from a single thermostat.



## DESCRIPTION

The RP971A Ratio Relay is a four port nonbleed pneumatic relay which produces a modulating pressure output proportional to pilot input changes. It is used to control pneumatic valve or damper actuators in sequence from a single thermostat.

## SPECIFICATIONS

**Model:**

RP971A Ratio Relay

**Operating Range:**

0 to 18 psi (0 to 124 kPa)

**Maximum Safe Air Pressure:**

30 psi (205 kPa)

**Ambient Operating Limits:**

Temperature: 0 to 140F (-18 to 60C)

Humidity: 5 to 95%

**Operating Air Pressures:**

Pilot: 3 to 15 psi (21 to 103 kPa)

Main: 18 psi (124 kPa)

**Air Handling Capacity:**

0.039 scfm at 1 psi differential (18 ml/s at 5 kPa differential)

**Air Consumption:**

0.002 scfm (0.8 ml/s) maximum

**Start Point:**

Adjustable from 0 to 10 psi (0 to 69 kPa)

**Pilot Operating Span:**

3 or 5 psi (20 or 35 kPa), nonadjustable

**Mounting:**

In line, wall, or panel mounted

**Air Connections:**

Barb type for 1/4-in. (6-mm) O.D. plastic tubing for Port 1 and 5/32-in. (4-mm) O.D. plastic tubing for Ports 2, 3, and 4

**Construction:**

Molded plastic with neoprene diaphragm, stainless steel valve seats, and 100-mesh stainless steel filters in main and branch ports

**Accessories:**

801629T Cable Clamp (2 in. [51 mm] dia) for wall mounting if desired

**Dimensions:**

2 in. (51 mm) dia x 2-5/8 (67 mm) deep

By using this Honeywell literature, you agree that Honeywell will have no liability for any damages arising out of your use or modification to, the literature. You will defend and indemnify Honeywell, its affiliates and subsidiaries, from and against any liability, cost, or damages, including attorneys' fees, arising out of, or resulting from, any modification to the literature by you.

**Home and Building Control**

Honeywell Inc.  
Honeywell Plaza  
P.O. Box 524  
Minneapolis MN 55408-0524

**Honeywell Latin American Division**

Miami Lakes Headquarters  
14505 Commerce Way Suite 500  
Miami Lakes FL 33016

**Home and Building Control**

Honeywell Limited-Honeywell Limitée  
155 Gordon Baker Road  
North York, Ontario  
M2H 2C9

**Honeywell Europe S.A.**

3 Avenue du Bourget  
B-1140 Brussels Belgium

**Honeywell Asia Pacific Inc.**

Room 3213-3225  
Sun Hung Kai Centre  
No. 30 Harbour Road  
Wanchai  
Hong Kong

---

**Honeywell**