



Non-Programmable Electric Heat Thermostats

US MODELS

T410 Electric Heating Thermostats



KEY FEATURES

- Includes long-lasting Micro Switch™ mechanism
- Easy to install – 6-in. (150-mm) color-coded leads
- Ideally suited to new construction applications
- Bimetallic temperature sensor
- One-piece cover with air vents
- Rugged plastic mounting base



ACCESSORIES:

272804A Range Stop and Locking Screws Assembly

	T410A1013	T410B1004
Ratings	22 A res. @ 120/208/240Vac 19 A res. @ 277 Vac	22 A res. @ 120/208/240Vac 19 A res. @ 277 Vac
Temperature marking	°F	°F
Color	Premier White®	Premier White®
Switching action	SPST	DPST
Setting temp. range	40°F to 80°F	40°F to 80°F
Differential temperature	3°F	3°F
Includes	---	Positive OFF

T4398 High Performance Electric Heating Thermostats



KEY FEATURES

- Extremely sensitive to temperature changes
- Integrated thermometer indicates room temperature
- Includes long-lasting Micro Switch™ mechanism
- Easy to install – 6-in. (150-mm) color-coded leads
- Vapor filled dual diaphragm
- Well-suited for upgrades and high-end new constructions
- Mounts directly on vertical 2 in. x 4 in. outlet box, or on 4 in. x 4 in. outlet box
- Rugged plastic mounting base



ACCESSORIES:

272804A Range Stop and Locking Screws Assembly

	T4398A1021	T4398B1029
Ratings	22 A res. @ 120/208/240Vac 19 A res. @ 277 Vac	22 A res. @ 120/208/240Vac 19 A res. @ 277 Vac
Temperature marking	°F	°F
Color	Premier White®	Premier White®
Switching action	SPST	DPST
Setting temp. range	50°F to 80°F	50°F to 80°F
Differential temperature	2°F	2°F
Includes	Thermometer, range stops and locking cover screws	Thermometer, range stops, locking cover screws and positive OFF

T498 Electric Heating Thermostats

Honeywell



KEY FEATURES

- Includes long-lasting Micro Switch™ mechanism
- Integrated thermometer indicates room temperature
- Easy to install – color-coded leads
- Well-suited for upgrades and high-end new constructions
- Bimetallic temperature sensor
- Rugged plastic mounting base
- Mount on 2 in. x 4 in. outlet box or on 4 in. x 4 in. junction box



ACCESSORIES:

272804A Range Stop and Locking Screws Assembly

	T498A1778	T498A1810	T498B1512	T498B1553
Ratings	22 A res. @ 120/208/240Vac 19 A res. @ 277 Vac	22 A res. @ 120/208/240Vac 19 A res. @ 277 Vac	22 A res. @ 120/208/240Vac 19 A res. @ 277 Vac	22 A res. @ 120/208/240Vac 19 A res. @ 277 Vac
Temperature marking	°F	°F	°F	°F
Color	Premier White®	Brush Gold Finish	Brush Gold Finish	Brush Gold Finish
Switching action	SPST	SPST	DPST	DPST
Setting temp. range	40°F to 80°F	40°F to 80°F	40°F to 80°F	40°F to 80°F
Differential temperature	3°F	3°F	3°F	3°F
Includes	Range stops and locking cover and extra knob decal for recalibration	---	Positive OFF, Range stops, locking cover and extra knob decal for recalibration	Positive OFF

Learn More

For more information call toll-free 1-800-328-5111,
e-mail us at info@honeywell.com or visit
us online at <http://yourhome.honeywell.com>

Automation and Control Solutions

In the U.S.:

Honeywell

1985 Douglas Drive North

Golden Valley, MN 55422-3992

In Latin America:

Honeywell

9315 NW 112th Avenue

Miami, FL 33178

www.honeywell.com

50-1361 GK
November 2008
© 2008 Honeywell International Inc.

Honeywell